

4G HD IR PTZ-WP-M91ST

4G HD IR PTZ Camera is a professional HD IR PTZ camera integrated with record, HD video wireless transmit, audio ,talk and remote control. It adopts high speed processor hardware and embedded Linux system. The state of the art HD camera use the latest IT technologies, such as H.264 codec, wireless transmitting technologies, remotely control etc. This powerful camera can be deployed on wireless and temporary outdoor surveillance application like police, traffic, or concerts, others.



Key features :

- Industrial-grade and integrated design for reliable working on harsh environment
- H.264 high profile compression
360 degree PTZ 20X/30X, 200 preset , auto cruising
.....Built-in battery power supply(4-6 hours work) or external power
- Support 1pcs SD card up to 256G for record storage
- 4G/WIFI transmit; multiple grade image quality transmitting option
- GPS/BD/GLONASS global positioning
- Powerful software platform including remote live, playback, broadcast, talk and more
- Power Supply/Outside support GPS/BD/GLONASS

Specification :

Industrial design

Integrated industrial design

User interface		Support E-set , remote controller, remotely operation, SD card ,etc to configure
Language		English (option customized)
Security		User password, Administrator password management
Video & Live	Input/output	1channel 720P(1280x720)video input, 1 channel video output ; 1.0Vp-p, 75Ω
	OSD	Overlays letters... like date /time into the video
	Compression	H.264 High Profile Compression
	Dual stream	Record with HD video and remotely live view with lower stream
	Live	1 channel
	Speed(frame rate)	PAL: 25fps , NTSC: 30fps
	Resolution	720P 、 D1、 CIF adjustable
	Image quality	High, middle, and low option
	Video rate	CIF : 384 kbps、 512 kbps、 768 kbps、 1024 kbps、 1536 kbps , 5 grades adjustable D1 : 512kbps、 768kbps、 1024kbps、 1536kbps、 2048kbps , 5 grades adjustable 720P : 1024kbps、 2048kbps、 3072kbps、 4096kbps、 5120kbps , 5 grades adjustable
Audio	Audio input/output	1 channel audio input/1 channel audio output;
	Compression	G.726
Record	Storage	Support 1pcs SD card up to 256G; option for SSD expandable
	Format	ASF/FAT32
	Record strategy	Default power-on record,
Zoom		20X/30X
IR Distance		>60 meters
Protocol		Pelco D/P
Speed		360°rotation; 120°/s
Vertical speed		-15°-90° vertical: 60°/S

3G/4G/WIFI		Support 3G/4G and compatible with GPRS,EDGE, etc; built-in WIFI, support hotspot
GPS (option)		Support GPS, option/BD/GLONASS
Firmware upgrading		SD card ; remotely upgrade;
Power supply	Battery	Built-in battery, working time: 6-8 hours ; External power supply: 19V/3A
	Battery Usage display	0/25%/50%/75%/100%
Work Environment	Temperature	-25°C ~ +70°C
	Humidity	10% ~ 95%
Installation		Sucker installation ; Fixed chassis installation(option); able-elevated bracket installation(option)
Waterproof grade		IP66
Size		128(W) x 40(H) x 135(D) mm(with bracket installation)
		104(W) x 40(H) x 135(D) mm(No bracket installation)
		Note: the specification is subject to change without prior notice.



