

**720P 4CH HD Dual SD Card Mobile DVR**

Model Number: WP-4M12HST

Video input: 4 Channels

Video output: 1ch CVBS

Audio input: 2 Channel audio input

Audio output: 1 Channel Audio Output

Video compress: H.264

Storage: Support Up to 512G SD card

Resolution: 720P

Key features :

- ◆Industrial-grade design with super mini size
- ◆Wide voltage support over-load ,short circuit ,reverse connect protection
- ◆Support Dual SD card up to512G for record storage
- ◆4G/WIFI transmit; multiple grade image quality transmitting option
- ◆GPS/BD/GLONASS global positioning
- ◆Powerful software platform including remote live, playback, broadcast, talk and more
- ◆IP communication
- ◆PTT group talk function

Specification

Industrial design		Mini size; Secure and reliable with high reliable interface design
User interface		Support E-set, remote controller, remotely operation, SD card, etc to configure
Language		English, Chinese (option customized)
Security		User password, Administrator password management
Video & Live	Input/output	4 channel video input, 1 channel video CVBS output; 1.0Vp-p, 75Ω
	OSD	Overlays letters, like date /time, vehicle ID, GPS, etc into the video
	Compression	H.264 High Profile Compression
	Dual stream	Record with HD video and remotely live view with lower stream
	Live	1 channel / Quad live; Support events triggered to full screen and video switch
	Speed(frame rate)	PAL: 100fps, each channel up to 25fps; NTSC: 120fps, each channel up to 30fps
	Resolution	720P /D1/CIF adjustable
Audio	Image quality	High, middle, and low option
	Video rate	CIF: 384 kbps, 512 kbps, 768 kbps, 1024 kbps, 1536 kbps, 5 grades adjustable D1: 512kbps/768kbps/1024kbps/1536kbps/2048kbps, 5 grades adjustable 720P: 1024kbps, 2048kbps, 3072kbps, 4096kbps, 5120kbps, 5 grades adjustable
	Audio input/output	2 channel audio input; 1 channel audio output;
Record	Compression	G.726
	Storage	Support 2pcs SD card up to 512G
Alarm	Format	ASF/FAT32
	Record strategy	Default power-on record, also support time schedule record, alarm record and events trigger record
3G/4G/WIFI	Input	3 channel level signal input
	Output	1 channel level signal output
		hotspot

GPS		Support GPS, option/BD/GLONASS			
System upgrade		SD card ; remotely upgrade;			
Power supply & consumption	Power manage	ACC on/off; delay off			
	Voltage input	DC:+8V ~ +36V			
	Voltage output	+12V@2.5A			
	Consumption	Working: <10W;			
Work	Temperature	-25°C ~ +60°C			
Environment	Humidity	10% ~ 95%			
Size		118 x 146 x 42 mm (with bracket installation) 146 x 146 x 42 mm (No bracket installation)			
Order type, such as:WP-4M10HST-SGWE-CX	2 Storage S:1pcs D:2pcs	3 Positioning N:NO G:GPS B:BD	4 WIFI N:NO A:AP W:WIFI	5 Network mode W:WCDMA E:EVDO WE : All network	6 Language C:Chinese E:English
Specifications are subject to change without prior notice					



